

2901 Series | Promotional Paint Mask, Low-Tack Removable Adhesive

Lumina® series 2901 is a calendered vinyl film designed for use as a paint mask. This product features a low-tack removable adhesive, which provides a light bond with clean removal from most OEM painted surfaces. To order punched material, use part number 2951.

Film Technology | Calendered (PVC)

Film Thickness | 3.4 mil

Color | Yellow (006)

Outdoor Durability | No

Finish | Matte

Blockout | No

Adhesive | Low- Tack Removable/ Clear

Liner | 78#

Conformability | Flat Surfaces and Simple Curves

Shelf Life | 1 Year

Bake cycle maximum temperature | 110°F

<u>CUTTING</u>	<u>PRINTING</u>	<u>INSTALLATION</u>
Computer Cut Yes Steel Rule Yes Thermal Die Yes Flat Bed Yes Sheetable Yes Laminate No	Thermal Transfer No Solvent No Eco-Solvent No Latex No UV No Screen No	Wet Apply No Min. App. Temp. 40°F Interior / Exterior Yes

<EN>

<p><u>FILM</u></p> <ul style="list-style-type: none"> • Film Thickness__ (mils/μm) 3.4 / 86 (+/- 10%) • Film Weight__ (gsm) 120 • Gloss__ 60° <20 • Opacity__ (%) 96 • Tensile Strength__ (lbs/in) MD > 3200 / CD > 2600 • Elongation__ (%) MD > 90 / CD > 150 • Dimensional Stability__ MD < 0.20 mm / CD < 0.10 mm 	<p><u>ADHESIVE</u></p> <ul style="list-style-type: none"> • Adhesive Type__ Emulsion Acrylic • Adhesive Thickness__ (mils/μm) 0.7-0.9 / 18-23 • Adhesive Color__ Clear • Peel Strength__ (lbs/in) 24 hrs
<p><u>LINER</u></p> <ul style="list-style-type: none"> • Liner Weight__ (#/gsm) 78 / 127 • Liner Type__ White Clay Coated Kraft • Liner Thickness__ (mils/μm) 4.5 / 114 • Release Force__ @ 360" / min (g/2") 40-60 	<p><u>PERFORMANCE GUIDANCE</u></p> <ul style="list-style-type: none"> • Application Temp.__ Room Temperature • Service Temp.__ N/A • Shelf Life__ 1 year • Storage Temp. / Rel. Humidity__ 70 °F / 50% • Outdoor Durability__ Not formulated for exterior usage

WARRANTY - Data provided by FDC Graphic Films, Inc. is for general information only. This data is not to be used for exacting specification purposes. Always pre-test the product. Suitability for any given application is the responsibility of the user. Since FDC Graphic Films, Inc. cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety, or applicability with respect hereto. FDC Graphic Films, Inc.'s only obligation shall be to replace such a quantity of product proven to be defective. FDC Graphic Films, Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC Graphic Films, Inc., shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, to short or reduced supply of fuel, or other integral components of the product.

<EN>