

7262 Series | Lumina Print Media: Static Cling White/Clear

Lumina series 7262 is a calendared static cling vinyl film in white and clear colors for the installation of graphics and decals on window. Its unique construction makes positioning and installation easy. The static cling adhesion system makes for clean and easy removal for temporary applications to exterior glass, up to 3 months. Temperature, wind, and rain may also limit the bond of static cling vinyl to exterior windows.

Film Technology | Static Cling Vinyl (Monomeric)

Film Thickness | 7 mil

Color | White/Clear

Outdoor Durability | 3 months (on glass)

Finish | Gloss

Blockout | No

Adhesive | No

Liner | 90#

Conformability | Flat

Shelf Life | 6 Months

<u>CUTTING</u>	<u>PRINTING</u>	<u>INSTALLATION</u>
Computer Cut Yes Steel Rule Yes Thermal Die No Flat Bed Yes Sheetable Yes Laminate No	Thermal Transfer No Solvent Yes Eco-Solvent Yes Latex Yes UV Yes Screen Yes	Wet Apply No Min. App. Temp. 40°F Interior / Exterior Yes

<MA>

<p><u>FILM</u></p> <ul style="list-style-type: none"> • Film Thickness__ (mils/μm) 7.0 / 179 (+/- 10%) • Film Weight__ (gsm) 220 • Gloss__ 60° Reflection (90 Gloss Units) • Opacity__ (%) N/A • Tensile Strength__ (lbs/in) MD > 2500 / CD > 2000 • Elongation__ (%) MD > 300 / CD > 300 • Dimensional Stability__ (FTM 14) N/A 	<p><u>ADHESIVE</u></p> <ul style="list-style-type: none"> • Adhesive Type__ N/A • Adhesive Thickness__ (mils/μm) N/A • Adhesive Color__ N/A • Peel Strength__ (lbs/in) N/A
<p><u>LINER</u></p> <ul style="list-style-type: none"> • Liner Weight__ (#/gsm) 90 / 145 • Liner Type__ White 2-Sided PE-Coated Kraft • Liner Thickness__ (mils/μm) 6.7 / 170 • Release Force__ @ 360" / min (g/2") 25-30 	<p><u>PERFORMANCE GUIDANCE</u></p> <ul style="list-style-type: none"> • Application Temp.__ On clean, dry substrate > +40 °F • Service Temp.__ -40 °F to 200 °F • Shelf Life__ 6 Months • Storage Temp. / Rel. Humidity__ 70°F (21°C) and 50% relative humidity • Outdoor Durability__ Up to 3 Months • Removability__ Up to 3 Months

NOTE - For further information regarding printing, substrate cleaning, application, maintenance, durability, and removal please review the corresponding instructional bulletin available at fdcfilms.com.

WARRANTY - Data provided by FDC Graphic Films, Inc. is for general information only. This data is not to be used for exacting specification purposes. Always pre-test the product. Suitability for any given application is the responsibility of the user. Since FDC Graphic Films, Inc. cannot control the conditions under which the products referred to herein may be used or handled, it can make no guarantee as to the effectiveness, safety, or applicability with respect hereto. FDC Graphic Films, Inc.'s only obligation shall be to replace such a quantity of product proven to be defective. FDC Graphic Films, Inc. shall not be liable for any injury, loss, or damage, direct or consequential, arising out of the use of or inability to use the product. Before using, the user shall determine the suitability of the product for their intended use, and the user assumes all risk and liability whatsoever in connection therewith. The seller, FDC Graphic Films, Inc., shall not be liable for any default or delay caused by contingency beyond its control or the control of its supplier including but not limited, to short or reduced supply of fuel, or other integral components of the product.

<MA>