

TransferRite®

Product Selection Guide

Sign makers, screen printers and commercial graphics professionals around the world rely on TransferRite® products to help them get the job done right.

We are proud that our products are the brand of choice for professionals like you. Whatever your application, we know you'll find the right product - and the right performance - in our family of tapes.

Sign

PRODUCT NUMBER	TACK LEVEL	THICKNESS PSTC-33 (mils)	ELONGATION PSTC-31 (%)	PRODUCT HIGHLIGHTS AND RECOMMENDED USES
560U	Low	4	2%	Superior adhesion to liner; For use on poster board and card stock
582U	Medium	4	2%	Superior adhesion to liner; Medium tack workhorse for general use
592U	High	4	2%	Superior adhesion to liner; Recommended for use with intermediate or calendered films
782U	Medium	5	6%	Superior adhesion to liner; Medium tack premium workhorse; Performs well in wet applications
6798	Very High	6	5%	Recommended for use with reflective films, awning material and etched glass films
1310	Medium	4	750%	Ultra clear film with Ultra adhesive for drop shadows and multicolor alignments; Tears easily; Doesn't grab banner material or corrugated plastic; Recommended for use with intermediate and calendered films
1320	High	4	750%	Ultra clear film for use with SignGold, etched glass films; Recommended for tiny lettering and graphics
1510	Medium	4	570%	Frosted clear film for drop shadows and multicolor alignments
7505	Medium	5	380%	Reusable film for use in application frames
8510	Medium	3	500%	Outdoor durable, UV-resistant (up to 6 months) blue film for finished sign protection

Digital

PRODUCT NUMBER	TACK LEVEL	THICKNESS PSTC-33 (mils)	ELONGATION PSTC-31 (%)	PRODUCT HIGHLIGHTS AND RECOMMENDED USES All products available up to 60" wide
6560	Low	4	2%	ProtectRite Digital standard paper; Economically priced
1301	Low	4	750%	Application film that adheres to exposed smooth release liners
6882	Medium	6	6%	ProtectRite Digital premium paper; Strong and versatile
AirMask	Medium	4	570%	Film premask that adheres to exposed air-release liners and removes effortlessly from printed vinyl; Recommended for application with a laminator
8510	Medium	3	500%	Outdoor durable blue film for flatbed print protection

RV, Fleet and Marine

PRODUCT NUMBER	TACK LEVEL	THICKNESS PSTC-33 (mils)	ELONGATION PSTC-31 (%)	PRODUCT HIGHLIGHTS AND RECOMMENDED USES
560U	Low	4	2%	RV paint mask installation
760U	Low	5	6%	Large, one-piece decals; RV paint mask installation; Unprinted vinyl parts; Digital prints
782U	Medium	5	6%	Graphics requiring long-term storage; 3M cross reference SCPM3
792U	High	5	6%	Fine plotter and die cut graphics; 3M cross reference SCPS2
6882	Medium	6	6%	Decals printed with UV inks; Digital prints
AirMask	Medium	4	570%	Film premask that adheres to exposed air-egress liners
992U	High	7	6%	Paper premask that adheres to exposed air egress liners

Specialty

PRODUCT NUMBER	TACK LEVEL	THICKNESS PSTC-33 (mils)	ELONGATION PSTC-31 (%)	PRODUCT HIGHLIGHTS AND RECOMMENDED USES
Awards & Engraving				
582U	Medium	4	2%	Laser masking for smooth surfaces
592U	High	4	2%	Laser masking for textured surfaces
Textile				
PM-12	Medium	4	2%	Pallet mask for textile screen printing simplifies spray adhesive clean-up; Eliminates the need for cleaning solvents and hazardous rag disposal
Paint Mask				
PM-50	Medium	4		Vinyl paint mask for low temperature bake cycles <110°F; Resists urethanes and acrylic enamels; Removes cleanly
StencilRite 6932	High	8	6%	A heavy paper tape laminated to a crepe liner for steel rule die cutting; Excellent paint hold out; Also used as a substrate for set design and temporary displays

